


single with Teflon insulated lead wire



Specifications:

Probe type	:	mineral insulated single thermocouple
Thermocouple type	:	iron-constantan, type J chromel-alumel, type K copper-constantan, type T
Insulation material	:	densely packed MgO, 99,6 purity
Tolerance	:	ASTM E230/ANSI MC96.1: Standard tolerance IEC 60584: Class 2
Sheath material	:	SS 316 for J and T Inconel 600 for type K
Hot junction	:	insulated
Minimum insulation resistance	:	10 Mohm at ambient temperature with 200 V DC
Lead wire	:	Teflon insulated copper braided and twisted flexible lead wire (TEX/CUTEXTW); positive wire identified with polarity mark
Upper temperature limit for lead wire	:	200 °C
Max. temperature transition	:	200 °C
Probe length 'A'	:	to be specified; replace box in ordering code with your required length
Lead wire length 'B'	:	to be specified; replace box in ordering code with your required length
For accessories	:	see separate datasheet

See B/100 for explanation of codes and alternative constructions.

Ordering code:

Probe diameter	Calibration J	Calibration N	Calibration K	Calibration T
	'A' 'B'		'A' 'B'	'A' 'B'
1,0 mm (1/25")	MTS-50101-J-□-□-MM	MTS-50103-N-□-□-MM	MTS-50103-K-□-□-MM	MTS-50101-T-□-□-MM
1,6 mm (1/16")	MTS-50161-J-□-□-MM	MTS-50163-N-□-□-MM	MTS-50163-K-□-□-MM	MTS-50161-T-□-□-MM
3,2 mm (1/8")	MTS-50321-J-□-□-MM	MTS-50323-N-□-□-MM	MTS-50323-K-□-□-MM	MTS-50321-T-□-□-MM
4,8 mm (3/16")	MTS-50481-J-□-□-MM	MTS-50483-N-□-□-MM	MTS-50483-K-□-□-MM	MTS-50481-T-□-□-MM
6,4 mm (1/4")	MTS-50641-J-□-□-MM	MTS-50643-N-□-□-MM	MTS-50643-K-□-□-MM	MTS-50641-T-□-□-MM

□ = probe length 'A' and lead wire length 'B' in mm (to be specified)